

Contractor Breakers



Our contractor breaker range has been designed where overall project cost is key, they offer unrivalled value for money to the rental and construction sectors. These versatile breakers are fully approved and tested for flow, pressure, compatibility and fitment as part of every machine development programme we carry out.

- Accumulators ensure that machines are completely protected from hydraulic pressure spikes
- Available as side mount, top mount or universal for non JCB machinery
- Moil & chisel tool provided as standard
- Vibro isolation rubber buffers absorb repercussion from hammering to reduce damage to the carrier machine
- Maintained using hand held greasing gun
- Comes with gas charging kit unless stated otherwise

Breaker tools

	HM018T	HM026T	HM033T	HM049T
Moil	334/C6976	334/G8302	332/A3062	400/C2450
Chisel (Cross cut/H)	334/C6978	334/G8335	332/A3063	400/C2451
Transverse chisel (Wedge in line /V)	335/H7422	334/G8352	332/A3064	400/C4253
Conical moil	-	334/G8299	332/A3061	-
Blunt (End flat)	335/H7423	334/G8358	332/A3065	400/C2454



Part number	Pin kit part number	Pickup mount	Pin size mm	Operating weight kg	Blow rate - Long stroke bpm	Tool diameter mm	Oil flow l/min	Pressure bar	Impact energy j	Noise level dBA
HM018T - 1CX/1CXT										
980/B0263	-	Side	35	165	600-1500	57	23-70	90-120	560	125
HM026T - 3CX Compact/2CX/Midi CX										
980/B0256	-	Side	32	234	380-1000	70	29-65	110-165	1072	125
HM033T - 3CX/4CX/5CX										
980/B0331	980/A5083	Side	45	415	380-900	75	34-76	120-165	1393	120
980/B0250*	980/A5083	Side	45	359	380-900	75	34-76	120-165	1393	120
HM033T - HD110W/8052 - 8086 65R - 100C										
980/B0251	980/A5083	Top	45	403	380-900	75	34-76	120-165	1393	120
HM049T - 4CX/5CX										
980/B0105	980/A5083	Side	45	420	400-800	80	38-85	140-170	1806	125

Universal options - No hanger bracket or hoses

Part number	Operating weight kg	Blow rate - Long stroke bpm	Tool diameter mm	Oil flow l/min	Pressure bar	Impact energy j	Noise level dBA
HM018T - 1.5-4.0 Tonnes							
980/B0262	187	600-1500	57	23-70	90-120	560	125
HM026T - 3.0-6.5 Tonnes							
980/B0255	260	380-1000	70	29-65	110-165	1072	125
HM033T - 4.5-8.0 Tonnes							
980/B0330	330	380-900	75	34-76	120-165	1393	120
980/B0253*	330	380-900	75	34-76	120-165	1393	120

*No gas kit

-The impact energy figures are based on calculations and may not be representative to application