

## Vehicle description for: TGS 28.480 6x2=2 BL CH



Illustration can deviate

### Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 28.480 6x2=2 BL CH
Engine family	D26
Vehicle type	Vehicle type, platform truck and chassis (LK)
Cab	Local transport cab NN
Main wheel distance	5100 mm
Overhang	2800 mm
Steering configuration	Left

### Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	26,000 kg	26,000 kg	26,000 kg
Front axle	8,000 kg	8,000 kg	8,000 kg
Rear axle	12,600 kg	13,000 kg	13,000 kg
Trailing axle	9,700 kg	10,000 kg	10,000 kg

### Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg

The printed images in this offer are for explanatory purposes and may differ from the actual configuration.  
For further product information on the tire selection "selectively", please contact our sales staff.

### Vehicle characteristics

#### Basic characteristics

<input type="checkbox"/>	Vehicle version municipal/public service deployment	0P0H7
<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P3HK
<input type="checkbox"/>	Merchant tonnage 28 t	0P8LI
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, normal height	0P2TS
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in English	0P2L7
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Cab position 640 mm (distance from frame lower edge to cab floor)	0PHBE

#### Registration

<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 89 km/h, tolerance +1 km/h, electronic, engine speed regulation	0P2UJ
<input type="checkbox"/>	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Maximum vehicle width of 2,500 mm checked with respect to relevant chassis components	0PIOJ
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

#### Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

#### Application scope / transport tasks

<input type="checkbox"/>	Distribution transport, general cargo	0P6WA
<input type="checkbox"/>	110 Tanker vehicle (fuel, combustibles, dangerous goods)	0P2R5
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

#### Horizontal and vertical loads

<input type="checkbox"/>	26,000 kg permitted gross load, vertical, nat. appr.	0P5P2
<input type="checkbox"/>	26,000 kg permitted gross load, vertical, tech.	0P5TV
<input type="checkbox"/>	26,000 kg permitted gross load, vertical, tech. Plus	0P8HJ
<input type="checkbox"/>	8,000 kg permitted load on front axle, nat. appr.	0P5KT
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech.	0P5LN
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech. Plus	0P8D4
<input type="checkbox"/>	12,600 kg permitted load on rear axle NatZu	0P5HB
<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech.	0P5IO
<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech. Plus	0P8BY
<input type="checkbox"/>	9,700 kg permitted load on trailing axle, nat. appr.	0P5JE
<input type="checkbox"/>	10,000 kg permitted load on trailing axle, tech.	0P5J0
<input type="checkbox"/>	10,000 kg permitted load on trailing axle, tech. Plus	0P8CY

- |                          |             |       |
|--------------------------|-------------|-------|
| <input type="checkbox"/> | 0kN D value | 0P8XD |
|--------------------------|-------------|-------|

**Notification texts**

- |                          |   |       |
|--------------------------|---|-------|
| <input type="checkbox"/> | Notice: Reduced front overhang angle due to long radiator | 0PHPG |
|--------------------------|---|-------|

**Chassis**

**Vehicle frame (wheelbase, overhang, ...)**

- |                          |   |       |
|--------------------------|---|-------|
| <input type="checkbox"/> | Main wheelbase, 5,100 mm                                | 0P3A4 |
| <input type="checkbox"/> | Wheelbase between rear axle and trailing axle, 1,350 mm | 0P3BR |
| <input type="checkbox"/> | Frame overhang, rear, 2,800 mm                          | 0P3E9 |
| <input type="checkbox"/> | Main frame side member thickness, 8 mm                  | 0P0Y6 |
| <input type="checkbox"/> | Vehicle rear, straight end of frame                     | 0P0XT |

**Exhaust system, air intake**

- |                          |                                     |       |
|--------------------------|-------------------------------------|-------|
| <input type="checkbox"/> | Exhaust silencer, side, left        | 0P1BG |
| <input type="checkbox"/> | Exhaust tailpipe, towards rear      | 0P1BQ |
| <input type="checkbox"/> | Air intake, behind cab, raised      | 0P0AY |
| <input type="checkbox"/> | Pre-separator for engine air intake | 0P0BA |

**Battery cases, batteries, alternator**

- |                          |  |       |
|--------------------------|--|-------|
| <input type="checkbox"/> | Battery, 12 V, 175 Ah, 2 units, maintenance free | 0P0WA |
| <input type="checkbox"/> | Alternator, Basic                                | 0P1BV |
| <input type="checkbox"/> | Medium battery box, 2 batteries                  | 0P0WU |
| <input type="checkbox"/> | Battery box, left                                | 0P0WO |
| <input type="checkbox"/> | Battery emergency stop switch                    | 0P3JV |
| <input type="checkbox"/> | Safety cut-out                                   | 0P1V2 |
| <input type="checkbox"/> | Lockable battery box, with padlock               | 0P0WL |

**Tanks and fuel line**

- |                          |  |       |
|--------------------------|--|-------|
| <input type="checkbox"/> | Double tank connection                                   | 0P4G0 |
| <input type="checkbox"/> | Fuel tank capacity 390 l and 490 l, right                | 0P8MB |
| <input type="checkbox"/> | Fuel tank, right, aluminium                              | 0P4GM |
| <input type="checkbox"/> | Fuel tank, right, combination tank                       | 0P4GR |
| <input type="checkbox"/> | Tank cross-section, right, medium                        | 0P4HE |
| <input type="checkbox"/> | AdBlue tank capacity 75 l, right                         | 0P4D2 |
| <input type="checkbox"/> | AdBlue tank, right, in combination tank                  | 0P4HI |
| <input type="checkbox"/> | AdBlue tank, right, aluminium with plastic inner coating | 0P4HV |
| <input type="checkbox"/> | Fuel tank cap, lockable for master key system            | 0P4H5 |
| <input type="checkbox"/> | Cap for AdBlue tank, lockable                            | 0P4GE |

**Frame attachments**

- |                          |  |       |
|--------------------------|--|-------|
| <input type="checkbox"/> | Underride protection, front                        | 0P1FN |
| <input type="checkbox"/> | Without working platform                           | 0P0VH |
| <input type="checkbox"/> | Without underride protection, side                 | 0P1FG |
| <input type="checkbox"/> | Spare wheel, provisionally mounted                 | 0P1GR |
| <input type="checkbox"/> | Final cross member, with hole pattern 160 x 100 mm | 0P1SB |
| <input type="checkbox"/> | Without underride protection, rear                 | 0P1FB |
| <input type="checkbox"/> | Wheel chock, 1 unit, with retaining device         | 0P1FO |

- Without body attachment brackets/thrust plates 0P0X6

**Pneumatic brakes, compressed-air generation, brake system**

- Air compressor, 1-cylinder, 360 ccm 0P0AF
- Air dryer, heated 0P0B2
- Compressed-air treatment, pneumatically controlled 0P0AB
- Aluminium compressed-air tank 0P0XG
- Electronic brake system (EBS) 0P0BL
- Anti-lock braking system (ABS) 0P0BE
- Full brake assistant 0P0CM
- Without preparation for EBS Full control unit 0PHPM
- MAN EVBec high-performance engine brake, stages possible 0P0BW
- Disc brakes on front axle 0P1I9
- Disc brakes on rear axle 0P1I4
- Disc brakes on trailing axle 0P1I8
- Parking brake control, next to driver's seat 0P3KH
- Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle) 0PGBL
- MAN EasyStart immobiliser 0P1TF
- Brake lining thickness display, with brake lining wear warning 0P0BG
- Harmonisation of brake lining wear 0P0BI

**Lights and acoustic signals on the chassis (rear lights,....)**

- Rear lights 0P2AQ
- Protective cover for rear lights 0P6XS
- Acoust. Reversing warning system when reverse gear selected 0P3CD
- Light function test 0P2AD
- Side marker lights, LED 0P2BJ

**Driveline/running gear**

**Engine, radiator**

- Diesel engine MAN D2676 LF07, 353 kW (480 hp) output, 2,300 Nm torque, Euro 5 0P6BL
- Fuel filter, heated, for fuels up to Cleanliness Class 25 0PHIG
- Fuel pre-filter, with oil separator/water trap, heated 0P0AU
- Engine dry-air filter, with safety insert 0P0B8
- Ventilation, crankcase, closed 0P8PM
- Anti-noise skirt, engine 0P2E7
- Fan control for start of cooling with low coolant temperature (e.g. hot country) 0P0K5
- Reduction of dust swirl through radiator fan 0P1YE
- Engine cooler, extended 0P4XY
- Front radiator protection, grille 0P1VP
- Engine oil dipstick and digital oil level gauge 0P0B6
- Warning message for engine coolant level, with advance warning 0P0KA
- Antifreeze, down to -32 °C 0P0AK
- Flame-start system 0P0GD
- Service product level indicator and intake system vacuum 0P3KT

**Gearbox, clutch**

your mobility partner

<input type="checkbox"/>	MAN TipMatic 12.26 DD	0P5VS
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN EfficientRoll gearbox function	0P0ET
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	MAN TipMatic Manoeuvre driving program, manoeuvring feature	0P0FI
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry	0P0DT

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index J	0PFW2
<input type="checkbox"/>	Front axle tyres Pirelli 315/80R22.5 FR:01 TRIATHLON Steering-Short-haul TL	0PEXM
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
<input type="checkbox"/>	Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/>	Rear axle tyres Pirelli 315/80R22.5 TR:01 TRIATHLON Drive-Local TL	0PDSV
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 9.00x22.5	0P0MU
<input type="checkbox"/>	Trailing axle tyres Pirelli 315/80R22.5 TR:01 TRIATHLON Drive-Short-haul TL	0PEME
<input type="checkbox"/>	Rim type, trailing axle, steel, single-part	0P0OT
<input type="checkbox"/>	Rim size, trailing axle, 10-hole, 9.00x22.5	0P0N7
<input type="checkbox"/>	Spare wheel, in accordance with configuration for front axle tyres	0P0MH

Axles

<input type="checkbox"/>	6x2=2	0P3B6
<input type="checkbox"/>	Steering ratio, indirect	0P1JY
<input type="checkbox"/>	Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/>	Front axle, 8,200 kg, not driven, cranked, steered, not liftable	0P5ER
<input type="checkbox"/>	Mudguard, front axle	0P1AT
<input type="checkbox"/>	Splash guard mat on mudguard, front axle, longer at bottom	0P1XS
<input type="checkbox"/>	Rear axle, 13,000 kg, HY axle without drive shaft, straight, not steered, not liftable	0P4ZP
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Mudguard, rear axle, upper shell removable	0P1AM
<input type="checkbox"/>	Splash guard mat on mudguard, rear axle, longer at bottom	0P1XK
<input type="checkbox"/>	Trailing axle, 10,500 kg, not driven, cranked, not steered, liftable	0P4ZV
<input type="checkbox"/>	Twin tyre on trailing axle	0P1HQ
<input type="checkbox"/>	Mudguard, trailing axle with removable upper shell	0P1AR
<input type="checkbox"/>	Splash guard mat on mudguard, trailing axle, longer at bottom	0P1XO
<input type="checkbox"/>	Axle ratio, i = 2.85	0P0CU
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/air (BL)	0P2YC
<input type="checkbox"/>	Control unit for electronically controlled air suspension (VASC)	0P3K9
<input type="checkbox"/>	VASC parametrisation for automatic setting of normal level from 20 km/h	0P1KU
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 2-leaf, steel	0P1JD
<input type="checkbox"/>	Air suspension on rear axle	0P1J5
<input type="checkbox"/>	Air suspension on trailing axle	0P1J8

<input type="checkbox"/>	Spring load-bearing capacity front axle 8,000 kg	0P5C2
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 13,000 kg	0P5BV
<input type="checkbox"/>	Spring load-bearing capacity of trailing axle, 10,000 kg	0P5B8
<input type="checkbox"/>	Trailing axle relievable, moving-off aid with maximum speed limitation	0P1IM
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Shock absorbers on trailing axle	0P1LV
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, trailing axle	0P1LL
<input type="checkbox"/>	Wishbone	0P6ZR

## Cab

---

### Cab and cab exterior

---

<input type="checkbox"/>	Local transport cab NN	0P2DL
<input type="checkbox"/>	Cab mount, Comfort	0P1V9
<input type="checkbox"/>	Cab tilt mechanism, electric	0P1V5
<input type="checkbox"/>	Roof spoiler, 600 mm adjustment range	0P1X7
<input type="checkbox"/>	Roof spoiler adjustment upon delivery, transport position	0P1XA
<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, plastic	0P1SD
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, rigid	0P1UZ
<input type="checkbox"/>	Central locking, with remote control	0P1WR
<input type="checkbox"/>	Vehicle key, 2 units	0P3JT
<input type="checkbox"/>	No door extension	0P1WV
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

### Lights and acoustic signals on cab exterior (headlights, horn, ...)

---

<input type="checkbox"/>	Front headlights, LED	0P1ZO
<input type="checkbox"/>	Daytime driving lights, LED	0P2BP
<input type="checkbox"/>	Fog lights, LED	0P2AI
<input type="checkbox"/>	Cornering light, LED	0P1YG
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5

- Without revolving beacons at the rear of the vehicle 0PJRO

#### Mirrors and mirror replacements

- Exterior rear-view mirror, electrically adjustable 0P2CA
- Kerb mirror, right, electrically adjustable 0P2CG
- Front mirror, mechanical adjustment 0P2CJ
- Mirror housing, not painted 0P2CP
- Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm 0P2CT
- Preparation for rear-view camera, 2 units, one camera linked to reverse gear 0P2D3

#### Seats

- Seat covers, fabric, standard 0P2PQ
- Comfort driver's seat, air-sprung 0P2P2
- Driver's seat comfort arm rests 0PGT3
- Adjustment of seat belt height, driver's seat 0P4XQ
- Co-driver's seat, not sprung, with storage box 0P2OO
- Storage space, in seat bracket of co-driver's seat 0P2Q6
- Seat belt indicator, driver's side, acoustic and visual 0P2NB

#### Driver's workplace

- Multi-function steering wheel, adjustable height and angle 0P2GD
- Steering wheel, with parking position 0P2GE
- Steering lock, with electronic immobiliser 0P3K0
- Instrumentation, Basic km/h 0P3L3
- Tachograph Simulation Unit (TSU), instead of tachograph 0P2KY
- Tachograph, calibrated 0P2KG
- Socket, cab centre, 2 units, 12 V and 24 V 0P2HX
- Stowage compartment, open with two USB sockets, 5 V, charging only, to the right of climate control panel 0PGT7
- 2 pull-out cup holders in instrument panel 0P2FA
- Cigarette lighter 0P2IH
- Control panel MAN EasyControl Engine, 2 functions, operable from outside with door open 0PGB5
- Single DIN slots, 4 units, roof space, front 0P2FJ

#### Cab air-conditioning system

- Air-conditioning system, manual 0P2NU

#### Cab interior

- Colour scheme for interior styling, light 0P2I7
- Interior styling analogous to colour scheme 0PGBT
- Windscreen roller blind, internal 0P2FE
- Roller blind for door windows, internal, mechanical, driver's and co-driver's sides 0P2FG
- Interior light, central 0PHA6
- Reading light, 1 unit, driver's side 0P2IQ
- Entry lighting 0P2IO
- Entry handles, standard 0PHPK
- Door interior cladding, not washable 0P2IB
- 2 storage compartments, cab rear wall, behind driver's and co-driver's side and net on cab rear wall 0PGB8
- Storage, instrument panel in middle section, open 0P2HK

- Grab handle, above door, internal, 2 units, 1 right and 1 left 0P2G2

#### Accessories and tools

---

- Vehicle toolkit 0P2TX
- Warning triangle, 1 units 0P3FI
- Fire extinguisher, 2 kg, 1 ea., rear area of cab, inside, in vehicle documentation language 0P2YE
- Compressed-air connection, cab, with compressed-air hose and gun 0P2FM
- Jack, 12,000 kg 0P3F8

#### Intelligent Truck

---

##### Assistance systems

---

- Electronic Stability Program (ESP) 0P1TN
- Anti-slip control (ASR) 0P1T2
- Tempomat (cruise control, CC) 0P1TR
- Road speed limiter, adjustable, limiter (engine speed regulation) 0P0C3
- Advanced Emergency Brake Assist (EBA) 0P1U3
- Lane Guard System (LGS) 0P1TT

##### Infotainment (radio,...)

- MAN SmartSelect infotainment control with touchpad and direct access buttons 0P3KV
- MMT infotainment system, Advanced Mid 0P2M0
- MAN sound system 0P2MG
- Europe and Russia navigation map 0P2MX
- Smartphone integration 0P2NE

#### Bodies/Interfaces

---

##### Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

- Without trailer brake connection behind cab 0P1O3
- No fifth-wheel coupling 0P1RJ

##### Interfaces to trailer (e.g. trailer coupling, brake connections,...)

- Towing coupling at final cross member, ROCKINGER SK5 0P1MZ
- Towing coupling on final cross member 0P1SH
- Without trailer brake connection at end of frame, centre 0P1O0
- Without trailer socket at frame end 0P1OW
- Without trailer socket for anti-lock brake system (ABS) 0P1O9

##### Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

- Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab 0P2NA

##### PTOs

---

- PTO, gearbox-dependent, type NH/4c, without flange, f=0.97, position approx. 2:30 o'clock 0P4QW
- PTO, gearbox-dependent, for short-time operation less than 60 min 0P4VK
- PTO, gearbox-dependent, shiftable 0P4X9
- Without fan wheel for PTO, gearbox-dependent 0P4VR



- |                          |   |       |
|--------------------------|---|-------|
| <input type="checkbox"/> | Function parameters for PTO; gearbox-dependent, driving operation | 0P4WP |
| <input type="checkbox"/> | Sector-specific parameterisation, general                         | 0P4X0 |

### Paintworks

#### Paintwork, cab, top

- |                          |                           |       |
|--------------------------|---------------------------|-------|
| <input type="checkbox"/> | Top coating, cab          | 0P6YB |
| <input type="checkbox"/> | Top coating, roof spoiler | 0P6X3 |

#### Paintwork, cab, bottom

- |                          |  |       |
|--------------------------|--|-------|
| <input type="checkbox"/> | Textured coating, step units           | 0P6X9 |
| <input type="checkbox"/> | Textured coating, mudguard, behind cab | 0P6YG |
| <input type="checkbox"/> | Textured coating, bumper, plastic      | 0P6YP |

#### Paintwork, chassis

- |                          |   |       |
|--------------------------|---|-------|
| <input type="checkbox"/> | Top coating, chassis                      | 0P6YC |
| <input type="checkbox"/> | Top coating, rims, steel, white-aluminium | 0P6YL |

### Colour

- |                          |                           |                         |   |
|--------------------------|---------------------------|-------------------------|---|
| <input type="checkbox"/> | Top coating, chassis      | GRAPHITE BLACK RAL 9011 | W |
| <input type="checkbox"/> | Top coating, cab          | SEPIA BROWN RAL 8014    | A |
| <input type="checkbox"/> | Top coating, roof spoiler | SEPIA BROWN RAL 8014    | A |

## Technical data: TGS 28.480 6x2=2 BL CH / L89FAA05

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: Local transport cab NN

Drive Type: 6x2=2

<b>Lengths</b>		<b>mm</b>
TD071	Total length	10855.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	1350
TD064	Rear frame overhang	2800.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	10649.0
<b>Widths</b>		<b>mm</b>
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0
<b>Frame</b>		<b>mm</b>
TD009	Frame width at front	942.0
TD010	Frame width at the rear	762.0
TD078	Frame profile	270 x 85 x 8
<b>Heights</b>		<b>mm</b>
TD033	Maximum external height, unladen	3686.0
TD082	Total transport height, unladen	3154.0
TD034	Maximum external height, laden	3610.0
TD035	Frame height at theoretical rear wheelbase, unladen	1011.0
TD036	Frame height at theoretical rear wheelbase, laden	981.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	145.0
TD048	Lowering from driving position, rear	90.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-
<b>Circle dimensions</b>		<b>m</b>
TD055	Track circle diameter	20.8
TD056	Wall-to-wall turning circle diameter	22.6
<b>Weights/loads</b>		<b>kg</b>
TD026	Chassis weight with cab	Error: 204
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---

TD029	Payload	---
TD018	Statorily permissible gross vehicle weight	26000
TD025	Technically permissible gross vehicle weight	26000
TD031	Statorily permissible gross train weight	0
TD032	Statorily permissible trailer load	0