

Vehicle description for: TGS 40.480 6x6 BB SA



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 40.480 6x6 BB SA
Engine family	D26
Vehicle type	Vehicle type Semitrailer tractor (SA)
Cab	TN cab: the flexible one (narrow, long, normal height)
Main wheel distance	3900 mm
Overhang	700 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	40,000 kg	40,000 kg	40,000 kg
Front axle	9,000 kg	9,000 kg	9,000 kg
Rear axle	16,000 kg	16,000 kg	16,000 kg
Rear axle 2	16,000 kg	16,000 kg	16,000 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	45,000 kg	64,000 kg	90,000 kg

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Vehicle version for public service deployment	0P0H7
<input type="checkbox"/>	Semitrailer tractor	0P2UA
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Merchant tonnage 40 t	0P8LM
<input type="checkbox"/>	Basic layout of vehicle, especially for heavy-duty use and heavy payloads	0PGCW
<input type="checkbox"/>	Frame type, high	0P2TP
<input type="checkbox"/>	Vehicle type Semitrailer tractor (SA)	0P2UR
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in Arabic	0P2L0
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Signage in Arabic, additional	0P2JF
<input type="checkbox"/>	Cab position 720 mm (distance from frame lower edge to cab floor)	0PHBF

Registration

<input type="checkbox"/>	Vehicle approval, N3G class	0P3JS
<input type="checkbox"/>	Maximum speed limiter, 100 km/h, electronic, engine speed regulation	0P2UD
<input type="checkbox"/>	Maximum vehicle noise level, 82 dB in acc. with UN/ECE-R 51.02	0PIND
<input type="checkbox"/>	Maximum vehicle width of 2,500 mm checked with respect to relevant cab components	0PIOH
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

Application scope / transport tasks

<input type="checkbox"/>	Construction	0P6WH
<input type="checkbox"/>	087 Semitrailer tractor for deployment in agriculture, on-road transport up to field edge	0P2R0
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	40,000 kg permitted gross load, vertical, nat. appr.	0P5RB
<input type="checkbox"/>	40,000 kg permitted gross load, vertical, tech.	0P5UW
<input type="checkbox"/>	40,000 kg permitted gross load, vertical, tech. Plus	0P8IL
<input type="checkbox"/>	9,000 kg permitted load on front axle, nat. appr.	0P5KX
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech.	0P5LR
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech. Plus	0P8EA
<input type="checkbox"/>	16,000 kg permitted load on rear axle NatZu	0P5HI
<input type="checkbox"/>	16,000 kg permitted load on rear axle, tech.	0P5IU

your mobility partner

<input type="checkbox"/>	16,000 kg permitted load on rear axle, tech. Plus	0P8B4
<input type="checkbox"/>	16,000 kg permitted load on 2nd rear axle NatZu	0P5FS
<input type="checkbox"/>	16,000 kg permitted load on 2nd rear axle, tech.	0P5NF
<input type="checkbox"/>	16,000 kg permitted load on 2nd rear axle, tech. Plus	0P7TP
<input type="checkbox"/>	45,000 kg permitted gross train weight, national registration	0PBIO
<input type="checkbox"/>	64,000 kg permissible gross train weight TechH.	0PBW1
<input type="checkbox"/>	90,000 kg permitted gross train weight, Tech. Plus	0PBRB
<input type="checkbox"/>	0kN D value	0P8XD
<input type="checkbox"/>	With the registered technical gross train weight, the maximum possible gradeability is 9 %	0P9BA

Notification texts

<input type="checkbox"/>	Note: Max. 55,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case	0PFZT
<input type="checkbox"/>	Increased. Wear and reduction in service life of propshafts, regular checks necessary	0PJRU

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 3,900 mm	0P2ZK
<input type="checkbox"/>	Wheelbase between rear axles, 1,400 mm	0P3BX
<input type="checkbox"/>	Frame overhang, rear, 700 mm	0P3EQ
<input type="checkbox"/>	Main frame side member thickness, 9.5 mm	0P0Y7
<input type="checkbox"/>	Vehicle rear, angled end of frame	0P0XS
<input type="checkbox"/>	Semitrailer auxiliary frame	0P0XV

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, left	0P1BG
<input type="checkbox"/>	Exhaust tailpipe, towards rear	0P1BQ
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY
<input type="checkbox"/>	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/>	Battery, 12 V, 175 Ah, 2 units, maintenance free	0P0WA
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, electric	0P0WE
<input type="checkbox"/>	Safety cut-out	0P1V2
<input type="checkbox"/>	Lockable battery box, with padlock	0P0WL

Tanks and fuel line

<input type="checkbox"/>	Fuel tank capacity 590 l, right	0P4EL
<input type="checkbox"/>	Fuel tank, right, aluminium	0P4GM
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Fuel pre-filter position on the battery box	0PIW9

Frame attachments

<input type="checkbox"/>	Without underride protection, front	0P1FM
--------------------------	-------------------------------------	-------

your mobility partner

<input type="checkbox"/>	Working platform, with step	0P0VE
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Spare wheel, provisionally mounted	0P1GR
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Without underride protection, rear	0P1FB
<input type="checkbox"/>	Without body attachment brackets/thrust plates	0P0X6
Pneumatic brakes, compressed-air generation, brake system		
<input type="checkbox"/>	Air compressor, 2-cylinder, 720 ccm	0P0AI
<input type="checkbox"/>	Compressed-air treatment, pneumatically controlled	0P0AB
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS), Offroad, with additional off-road logic	0P0BF
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/>	Drum brakes on front axle	0P1IA
<input type="checkbox"/>	Drum brakes on rear axle	0P1I5
<input type="checkbox"/>	Drum brakes on 2nd rear axle	0P1IF
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Brake cylinder with parking brake for increased gross weight	0P8QF
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	Anti-jackknifing brake, manual, can be operated next to driver's seat	0P0CJ
Lights and acoustic signals on the chassis (rear lights,....)		
<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Emergency braking signal, hazard light activation, automatic	0P0CG
<input type="checkbox"/>	Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	Side marker lights, LED	0P2BJ

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D2676 LF03, 353 kW (480 hp) output, 2,300 Nm torque, Euro 2	0P6BO
<input type="checkbox"/>	Fuel filter, for fuels up to Cleanliness Class 21	0PHIH
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap	0P0AT
<input type="checkbox"/>	Without torque reduction	0P0G5
<input type="checkbox"/>	Engine dry-air filter, with safety insert	0P0B8
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Anti-noise skirt, engine	0P2E7
<input type="checkbox"/>	Engine radiator Visco fan, high cooling output	0P0H0
<input type="checkbox"/>	Fan control for start of cooling with low coolant temperature (e.g. hot country)	0P0K5
<input type="checkbox"/>	Reduction of dust swirl through radiator fan	0P1YE
<input type="checkbox"/>	Engine cooler, extended	0P4XY
<input type="checkbox"/>	Radiator protection, lower	0P1XE
<input type="checkbox"/>	Front radiator protection, grille	0P1VP
<input type="checkbox"/>	Engine oil dipstick and digital oil level gauge	0P0B6

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Warning message for engine coolant level, with advance warning | 0P0KA |
| <input type="checkbox"/> | Antifreeze, down to -32 °C | 0P0AK |
| <input type="checkbox"/> | Service product level indicator and intake system vacuum | 0P3KT |

Gearbox, clutch

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Manually operated gearbox, MAN 16.25 OD | 0P5VL |
| <input type="checkbox"/> | Gearbox for increased percentage of overrun during driving operation | 0PGCL |
| <input type="checkbox"/> | Manual gearbox operation, single-H, group/split switch | 0P3KL |
| <input type="checkbox"/> | Transfer case MAN G253 with on-road and off-road gear, neutral position | 0P4XN |
| <input type="checkbox"/> | Transfer case lock management, electronic (VSM) | 0P0FU |
| <input type="checkbox"/> | Double-disc clutch, 400 mm, dry, for high gross train weights | 0P0DY |
| <input type="checkbox"/> | Driveline propshaft, reinforced | 0P0E2 |
| <input type="checkbox"/> | Propshaft, 2nd rear axle, reinforced | 0PGCF |
| <input type="checkbox"/> | Gearbox heat exchanger | 0P0FW |

Wheels, tyres

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Required tyre speed index J | 0PFW2 |
| <input type="checkbox"/> | Tyres, front axle, Bridgestone 325/95R24 G584 special TT | 0PJH4 |



- | | | |
|--------------------------|---------------------------------------|-------|
| <input type="checkbox"/> | Rim type, front axle, steel, split | 0P0OZ |
| <input type="checkbox"/> | Rim size, front axle, 10-hole, 8.5-24 | 0P0NG |
| <input type="checkbox"/> | Wheel nut cover ring, front axle | 0P0PR |

- Tyres, rear axle, Bridgestone 325/95R24 G584 Special TT

0PJEO



- Rim type, rear axle, steel, split
- Rim size, rear axle, 10-hole, 8.5-24
- Tyres, 2nd rear axle, Bridgestone 325/95R24 G584 Special TT

0P0ON
0P0MS
0PJFJ



- Tyre tread G584, 2nd rear axle
- Rim type, 2nd rear axle, steel, split
- Rim size, 2nd rear axle, 10-hole, 8.5-24
- Spare wheel, in accordance with configuration for front axle tyres
- Centring sleeves for rim mounting

0PJBX
0P0P9
0P0O5
0P0MH
0PHZW

Axles

- 6x6
- Steering ratio, indirect
- Steering oil tank with electrical measuring sensor
- Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable
- Front axle as planetary axle, driven, engageable
- Mudguard, front axle

0P3BD
0P1JY
0P1JV
0P5ES
0P1GY
0P1AT

your mobility partner

<input type="checkbox"/>	Rear axle, 16,000 kg, planetary axle with drive shaft, straight, not steered, not liftable	0P4ZQ
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Mudguard, rear axle, plastic half shells in front of rear axle	0P1AO
<input type="checkbox"/>	2nd rear axle, 16,000 kg, planetary axle without drive shaft, straight, not steered, not liftable	0P4Y9
<input type="checkbox"/>	Twin tyre on 2nd rear axle	0P1HW
<input type="checkbox"/>	Mudguard, plastic half shells, behind 2nd rear axle, with transfer tarpaulin over both rear axles	0P1AY
<input type="checkbox"/>	Splash guard mat on mudguard, 2nd rear axle	0P1XY
<input type="checkbox"/>	Axle ratio, $i = 5.33$	0P0DD
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 3-leaf, steel	0P1JE
<input type="checkbox"/>	Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel	0P1J2
<input type="checkbox"/>	Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel	0P1JL
<input type="checkbox"/>	Spring load-bearing capacity front axle 9,500 kg	0P5C4
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 16,000 kg	0P5BW
<input type="checkbox"/>	Spring load-bearing capacity of 2nd rear axle, 16,000 kg	0P5C8
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Shock absorbers on 2nd rear axle	0P1M9
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, 2nd rear axle	0P1LH
<input type="checkbox"/>	Wishbone, reinforced	0P6ZS
<input type="checkbox"/>	Without trailer air suspension control	0PHN2

Cab

Cab and cab exterior

<input type="checkbox"/>	TN cab: the flexible one (narrow, long, normal height)	0P2DF
<input type="checkbox"/>	Cab mount, Basic	0P1V8
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	Roof spoiler, 600 mm adjustment range	0P1X7
<input type="checkbox"/>	Roof spoiler adjustment upon delivery, driving position	0P1X9
<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, hinged	0P1V0
<input type="checkbox"/>	Central locking, with remote control	0P1WR
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	Door extension, driver's and co-driver's side	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ

<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	Without light and headlight package	0PKWU
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Daytime driving lights with rear lights, H7	0P2BO
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, bulb, 2 units	0P2BT
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, halogen, yellow, with function monitoring	0P2B9
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Spotlight, 1 unit, cab roof, left	0P1YK
<input type="checkbox"/>	Spotlight, LED, white	0PJQA
<input type="checkbox"/>	Switch for spotlight/manoeuvring light	0P5U5
<input type="checkbox"/>	Preparation for lighting behind cab	0PHZU
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Without mirror package	0PKWV
<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable with manoeuvring aid	0P2CB
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Mirror housing, painted, cab colour	0P2CN
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Without driver's seat package	0PKXV
<input type="checkbox"/>	Comfort driver's seat, air-sprung, with lumbar support and shoulder adjustment	0P2P5
<input type="checkbox"/>	Driver's seat arm rests	0P2OE
<input type="checkbox"/>	Adjustment of seat belt height, driver's seat	0P4XQ
<input type="checkbox"/>	Without co-driver's seat package	0PKXU
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6
<input type="checkbox"/>	Seat belt indicator, driver's side, acoustic and visual	0P2NB

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Instrumentation, Basic km/h	0P3L3
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Socket, cab centre, 2 units, 12 V and 24 V	0P2HX

your mobility partner

<input type="checkbox"/>	2 pull-out cup holders in instrument panel	0P2FA
<input type="checkbox"/>	Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Standard control field, inside of driver's door, with door open operated externally, 4 function buttons	0P3KE
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/>	Without storage tray next to seat	0PJRS

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

<input type="checkbox"/>	Bunk, bottom, with slatted support	0P2GX
<input type="checkbox"/>	Standard bed mattress, bottom, 90 mm	0P2GM
<input type="checkbox"/>	Cross-cab curtain, rear seats	0P2GP
<input type="checkbox"/>	Storage box, rear left, accessible from outside with flap and from inside below suspended tray	0P2H0
<input type="checkbox"/>	Storage box, rear, right, accessible from outside with flap and from inside below suspended tray	0P2H4

Cab interior

<input type="checkbox"/>	Colour scheme for interior styling, dark	0P2I6
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Without driver's workplace package, Comfort	0PKXT
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Roller blind for door windows, internal, mechanical, driver's side	0P2FH
<input type="checkbox"/>	Carpet, on engine tunnel	0P2I9
<input type="checkbox"/>	Without interior lighting package	0PKNF
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Entry handles, standard	0PHPK
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Without stowage and storage space package	0PKXS
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	Storage compartment, below the bunk, with bulkhead	0P2HH
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2

Accessories and tools

<input type="checkbox"/>	Without accessories and tools package	0PKXA
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	First aid kit	0P3F3
<input type="checkbox"/>	No warning triangle	0P3FH
<input type="checkbox"/>	Fire extinguisher, 2 kg, 1 ea., rear area of cab, inside, in vehicle documentation language	0P2YE
<input type="checkbox"/>	Compressed-air connection, cab, with compressed-air hose and gun	0P2FM
<input type="checkbox"/>	Jack, 25,000 kg	0P3F9
<input type="checkbox"/>	Operator's manual in Arabic, printed, additional	0PHZY

Intelligent Truck

Assistance systems

your mobility partner

<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5
<input type="checkbox"/>	Without driving fitness detection system	0PHN5
<input type="checkbox"/>	Without Front Detection	0PHNA
<input type="checkbox"/>	Without traffic sign recognition	0PHNE
<input type="checkbox"/>	Without Reversing Motion System	0PHNV
<input type="checkbox"/>	Without distance warning system	0PKA0

Infotainment (radio,...)

<input type="checkbox"/>	Radio preparation, 12 V	0P2M4
<input type="checkbox"/>	Loudspeaker, door, 2 units, 1 left and 1 right	0P2ME
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	English additionally for display	0P2JQ

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	2-line semitrailer brake connection, behind cab, spiral cable with standard coupling	0P1O2
<input type="checkbox"/>	Socket for tankers behind cab, 24 V, 15-pin	0P1PH
<input type="checkbox"/>	Spiral cable to semitrailer, electr., one unit, for trailer socket behind cab, 24-V, 15-pin to 15-pin	0P8NY
<input type="checkbox"/>	Spiral cable to semitrailer, electric, for trailer socket ABS, behind cab	0P8O1
<input type="checkbox"/>	Fifth-wheel pick-up plate installation height, 40 mm (up to max. 36,000 kg fifth-wheel coupling load)	0P6ZZ
<input type="checkbox"/>	JOST JSK 38 C 3.5" fifth-wheel coupling	0P1RP
<input type="checkbox"/>	Kingpin, 3.5" diameter	0P1RZ
<input type="checkbox"/>	Manufacturer of fifth-wheel coupling: Jost	0PBY1
<input type="checkbox"/>	Fifth-wheel coupling installation height, 190 mm	0P1PT
<input type="checkbox"/>	Fifth-wheel coupling, manual lubrication	0P6XR
<input type="checkbox"/>	Rubber joint bearing, fifth-wheel coupling	0PBY6
<input type="checkbox"/>	Fifth-wheel coupling actuation, normal handle	0P1QI
<input type="checkbox"/>	Without sensing of the fifth-wheel coupling	0PHN7
<input type="checkbox"/>	Fifth-wheel lead, 1,075 mm	0P5AW

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
<input type="checkbox"/>	Towing coupling on final cross member	0P1SH
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Trailer socket for anti-lock braking system (ABS), behind cab	0P1O5

PTOs

<input type="checkbox"/>	PTO, gearbox-dependent, type NH/4c, without flange, f=1.17/1.40, position approx. 2 o'clock	0P4QJ
<input type="checkbox"/>	PTO, gearbox-dependent, for short-time operation less than 60 min	0P4VK
<input type="checkbox"/>	PTO, gearbox-dependent, shiftable	0P4X9
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP

Towing, recovery and lashing

- Central coupling jaw, integrated in bumper/front cross member, with lock pin

0P1MK

Paintworks

Paintwork, cab, top

- Top coating, cab

0P6YB

- Top coating, roof spoiler

0P6X3

Paintwork, cab, bottom

- Textured coating, door extension and step units

0P6YA

- Textured coating, mudguard, behind cab

0P6YG

- Textured coating, bumper, steel

0P6YQ

Paintwork, chassis

- Top coating, chassis

0P6YC

- Top coating, rims, steel, white-aluminium

0P6YL

Colour

- Top coating, chassis

GRAPHITE BLACK RAL 9011

W

- Top coating, cab

PURE WHITE RAL 9010

N

- Top coating, roof spoiler

PURE WHITE RAL 9010

A

Technical data: TGS 40.480 6x6 BB SA / L58JAA02

Vehicle type: Vehicle type Semitrailer tractor (SA)

Cab: TN cab: the flexible one (narrow, long, normal height)

Drive Type: 6x6

Lengths		mm
TD071	Total length	7715.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	700.0
TD072	Distance from first front axle to body	865.0
TD067	Distance to kingpin from front axle, nominal position	4225.0
TD074	Slew radius, front	3260.0
TD075	Slew radius, rear	2169.0
TD068	Coupling length	7549.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

Heights		mm
TD033	Maximum external height, unladen	4049.0
TD082	Total transport height, unladen	4049.0
TD034	Maximum external height, laden	3951.0
TD035	Frame height at theoretical rear wheelbase, unladen	1269.0
TD036	Frame height at theoretical rear wheelbase, laden	1186.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	1583.0
TD052	Height of fifth-wheel coupling above ground, laden	1500.0

Circle dimensions		m
TD055	Track circle diameter	18.5
TD056	Wall-to-wall turning circle diameter	20.1

Weights/loads		kg
TD026	Chassis weight with cab	11617.0
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---
TD029	Payload	---

TD018	Statutorily permissible gross vehicle weight	40000
TD025	Technically permissible gross vehicle weight	40000
TD031	Statutorily permissible gross train weight	45000
TD032	Statutorily permissible trailer load	0